



GF 90



GE 60 / GE 65



GE 100 / GE 115

Modell	GF 90	GE 60	GE 65	GE 100	GE 115
--------	-------	-------	-------	--------	--------

Programtid i min	2' 3,5' 10'	2' 4' 6' 8'	2' 4' 6' 8'	2' 4' 6' 8'	2' 4' 6' 8'
Vattenförbrukning slutsköljning 85°C	4 l	4 l	4 l	8 l	8 l
Vattenförbrukning / diskprogram	4 l	4 l	4 l	8 l	8 l
Tank volym	35 l	90 l	90 l	150 l	150 l
Effekt cirkulationspump	1,5 kW	2,2 kW	3 kW	2,2 + 2,2 kW	3 + 3 kW
Effekt tryckstegringspump			0,55 kW	0,55 kW	0,55 kW
Storlek på backar	500x600	650x700 mm	650x700 mm	1320x700 mm	1320x700 mm
Höjd på diskutrymme	500 mm	650 mm	650 mm	650 mm	650 mm
Effekt tankelement	3,0 kW	4,2 kW	4,2 kW	6,0 kW	6,0 kW
Effekt booster	6,0 kW	6,0 kW	6,0 kW	9,0 kW	9,0 kW
Total anslutningseffekt	7,50 kW	8,20 kW	9 kW	13,40kW	15,00 kW
Bredd	620 mm	830 mm	830 mm	1500 mm	1500 mm
Djup	735 mm	860 mm	860 mm	860 mm	860 mm
Höjd	1380 mm	1870 mm	1870 mm	1870 mm	1870 mm
Vikt	110 kg	200 kg	220 Kg	340 kg	360 kg